

DIMENSIONI - DIMENSIONS

| MODELLO MODEL | U.M. | A | W* | B | C | D | E | F | G | H | K | L | M | N | P | Q | R | ∅ S-S | T | U | V | ISO 5211 STD | ISO 5211 SPECIAL |
|------------------|------|-------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|-----------|------|------|-------------|--------|-----------|------|-----------------|---------------------|
| AP1 DA/SR | mm | 142 | 162 | 67 | 60 | 87 | 20 | 42 | 41 | 12 | 8 | - | 80 | 30 | 25 | 10 | 2 | 9/11** | M5/M6 | 36/50 | 1/8" | F03/F05 | F04 |
| | ins. | 5.59 | 6.38 | 2.64 | 2.36 | 3.43 | 0.79 | 1.65 | 1.61 | 0.47 | 0.31 | - | 3.15 | 1.18 | 0.98 | 0.39 | 0.08 | 0.35/0.43** | | 1.42/1.97 | | | |
| AP2 DA/SR | mm | 155 | 171 | 83 | 73 | 103 | 20 | 42 | 44.5 | 12 | 8 | - | 80 | 30 | 30/35 | 12 | 2 | 11/14** | M5/M6 | 42/50 | 1/4" | *** F04/F05 | — |
| | ins. | 6.10 | 6.73 | 3.27 | 2.87 | 4.06 | 0.79 | 1.65 | 1.75 | 0.47 | 0.31 | - | 3.15 | 1.18 | 1.18/1.38 | 0.47 | 0.08 | 0.43/0.55** | | 1.65/1.97 | | | |
| AP3 DA/SR | mm | 213 | 240 | 100 | 85 | 120 | 20 | 50 | 49.5 | 14 | 10 | - | 80 | 30 | 35 | 16 | 3 | 14/17** | M6/M8 | 50/70 | 1/4" | F05/F07 | — |
| | ins. | 8.33 | 9.45 | 3.94 | 3.35 | 4.72 | 0.79 | 1.97 | 1.95 | 0.55 | 0.39 | - | 3.15 | 1.18 | 1.38 | 0.63 | 0.12 | 0.43/0.67** | | 1.97/2.76 | | | |
| AP3.5 DA/SR | mm | 236 | 268 | 110 | 98 | 130 | 20 | 50 | 53 | 19 | 14 | - | 80 | 30 | 55 | 20 | 3.5 | 17/22** | M8 | 70 | 1/4" | F07 | F05/F07 |
| | ins. | 9.29 | 10.55 | 4.33 | 3.86 | 5.12 | 0.79 | 1.97 | 2.09 | 0.75 | 0.55 | - | 3.15 | 1.18 | 2.17 | 0.79 | 0.14 | 0.67/0.87** | | 2.76 | | | |
| AP4 DA/SR | mm | 276 | 304 | 125 | 110 | 145 | 20 | 50 | 58 | 19 | 14 | - | 80 | 30 | 55 | 20 | 3.5 | 17/22** | M8/M10 | 70/102 | 1/4" | F07/F10 | — |
| | ins. | 10.87 | 11.97 | 4.92 | 4.33 | 5.71 | 0.79 | 1.97 | 2.28 | 0.75 | 0.55 | - | 3.15 | 1.18 | 2.17 | 0.79 | 0.14 | 0.67/0.87** | | 2.76/4.02 | | | |
| AP4.5 DA/SR | mm | 310 | 350 | 142 | 128 | 172 | 30 | 58 | 69 | 28 | 20 | 130 | 80 | 30 | 70 | 24 | 3.5 | 17**/22 | M10 | 102 | 1/4" | F10 | F07 |
| | ins. | 12.20 | 13.78 | 5.59 | 5.04 | 6.77 | 1.18 | 2.28 | 2.72 | 1.10 | 0.79 | 5.12 | 3.15 | 1.18 | 2.76 | 0.94 | 0.14 | 0.67**/0.87 | | 4.02 | | | |
| AP5 DA/SR | mm | 366 | 405 | 155 | 140 | 185 | 30 | - | - | 28 | 20 | 130 | 80 | 30 | 70 | 24 | 3.5 | 17**/22 | M10 | 102 | 1/4" | F10 | F07/F12 |
| | ins. | 14.41 | 15.94 | 6.10 | 5.51 | 7.28 | 1.18 | - | - | 1.10 | 0.79 | 5.12 | 3.15 | 1.18 | 2.76 | 0.94 | 0.14 | 0.67**/0.87 | | 4.02 | | | |
| AP5.5 DA/SR | mm | 388 | 442 | 176 | 160 | 206 | 30 | - | - | 36 | 28 | 130 | 80 | 30 | 85 | 29 | 3.5 | 22**/27 | M12 | 125 | 1/4" | F12 | F10 |
| | ins. | 15.27 | 17.40 | 6.93 | 6.30 | 8.11 | 1.18 | - | - | 1.42 | 1.10 | 5.12 | 3.15 | 1.18 | 3.35 | 1.14 | 0.14 | 0.87**/1.06 | | 4.92 | | | |
| AP6 DA/SR | mm | 468 | 500 | 200 | 175 | 230 | 30 | - | - | 36 | 28 | 130 | 80 | 30 | 85 | 29 | 3.5 | 22**/27 | M12 | 125 | 1/4" | F12 | F10 |
| | ins. | 18.42 | 19.68 | 7.87 | 6.89 | 9.06 | 1.18 | - | - | 1.42 | 1.10 | 5.12 | 3.15 | 1.18 | 3.35 | 1.14 | 0.14 | 0.87**/1.06 | | 4.92 | | | |
| AP8 DA/SR | mm. | 563 | 612 | 250 | 215 | 300 | 50 | - | - | 48 | 32 | 130 | - | 30 | 100 | 38 | 5 | 27**/36 | M16 | 140 | 1/4" | F14 | F12 |
| | ins. | 22.16 | 24.09 | 9.84 | 8.46 | 11.81 | 1.97 | - | - | 1.89 | 1.26 | 5.12 | - | 1.18 | 3.94 | 1.50 | 0.20 | 1.06**/1.42 | | 5.51 | | | |
| AP10 DA/SR | mm. | 750 | 838 | 335 | 290 | 385 | 50 | - | - | 48 | 32 | 130 | - | 30 | 130 | 50 | 5 | 36**/46 | M20 | 165 | 1/4" | F16 | F14 |
| | ins. | 29.53 | 32.99 | 13.19 | 11.42 | 15.16 | 1.97 | - | - | 1.89 | 1.26 | 5.12 | - | 1.18 | 5.12 | 1.97 | 0.20 | 1.42**/1.81 | | 6.50 | | | |