


Dimensioni d'ingombro valvola a sfera con attuatore pneumatico a doppio effetto
Overall dimensions ball valve with pneumatic actuator - double acting

Diam/Size mm ins.	Modello Model	A	B	C	D	ØE	F	G	H	I	L	ØM	PESO WEIGHT Kg.	
8	1/4	AP0 - DA	65	115	45	29	32	17	22.5	22.5	25	110	11.5	0.82
10	3/8	AP0 - DA	65	115	45	29	32	17	22.5	22.5	25	110	15	0.82
15	1/2	AP1 - DA	65	137	67	29	32	17	41	30	25	137	15	1.12
20	3/4	AP1 - DA	75	144	67	32	40	19	41	30	25	137	20	1.24
25	1	AP1 - DA	86	151.5	67	36	47	21	41	30	25	137	25	1.62
32	1 1/4	AP1 - DA	95	161.5	67	41	57	22	41	30	25	137	32	1.91
40	1 1/2	AP2 - DA	101	199.5	83	57	69	22	44.5	36.5	25	150	38	2.79
50	2	AP2 - DA	120	213	83	64	82	25	44.5	36.5	25	150	47	3.62
65	2 1/2	AP3 - DA	165	266.5	100	85	113	30	49.5	42.5	25	204	65	7.02
80	3	AP3.5 - DA	188	297	110	94.5	135	33	53	49	25	230	80	10.39
100	4	AP4 - DA	225	349	125	116	166	39	58	55	25	271	100	15.86

Dimensioni d'ingombro valvola a sfera con attuatore pneumatico a semplice effetto
Overall dimensions ball valve with pneumatic actuator - spring return

Diam/Size mm ins.	Modello Model	A	B	C	D	ØE	F	G	H	I	L	ØM	PESO WEIGHT Kg.	
8	1/4	AP1 - SR	65	137	67	29	32	17	41	30	25	137	11.5	1.42
10	3/8	AP1 - SR	65	137	67	29	32	17	41	30	25	137	15	1.42
15	1/2	AP1 - SR	65	137	67	29	32	17	41	30	25	137	15	1.42
20	3/4	AP1 - SR	75	144	67	32	40	19	41	30	25	137	20	1.47
25	1	AP2 - SR	86	167	83	36	47	21	41	30	25	150	25	2.51
32	1 1/4	AP2 - SR	95	177	83	41	57	22	44.5	36.5	25	150	32	2.80
40	1 1/2	AP3 - SR	101	216	100	57	69	22	49.5	42.5	25	204	38	4.33
50	2	AP3 - SR	120	230	100	64	82	25	49.5	42.5	25	204	47	5.16
65	2 1/2	AP4 - SR	165	291	125	85	113	30	58	55	25	271	65	10.44
80	3	AP5 - SR	188	352	155	95.5	135	33	70	70	35	360	80	19.31
100	4	AP5 - SR	225	389	155	116	166	39	70	70	35	360	100	23.10

Dimensionamento attuatore:

- alimentazione aria attuatore 5.5 bar (80 psi) min. con un ΔP valvola 16 bar (232 psi) max.

Actuator sizing:

- air supply actuator 5.5 bar (80 psi) min. with ΔP valve 16 bar (232 psi) max.